



# AS 70 - INDUSTRIAL THREE PHASE



OEM ORIGINAL EQUIPMENT MANUFACTURERS



PACKAGING



PLASTICS



TEXTILE



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Low noise level
- ✓ Compact and mobile
- ✓ Conceived for packaging lines scraps and wastes suction
- ✓ Tank provided with large capacity nylon filtering bag
- ✓ Full customization for specific needs



## SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	5,5
Electrical protection	IP	55
Max water lift	mmH <sub>2</sub> O	3000
Max water lift	mmH <sub>2</sub> O	3000
Max air flow	m <sup>3</sup> /h	550
Suction inlet	mm	80
Noise level (EN ISO 3744)	dB(A)	71



## FILTER UNIT

Filter Type		Bag
Material - Efficiency	IEC 60335-2-69	Nylon - L



## COLLECTION UNIT

Capacity	lt	210
----------	----	-----



## VOLUME

Dimensions	cm	63x100x125h
Weight	kg	125



## SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



## FILTER UNIT

Thanks to the nylon filtering bag, a great quantity of light and voluminous material can be collected and easily disposed. A transparent rear window on the upper cover allows to keep the filling level of the filtering bag under control.



## COLLECTION UNIT

The material is vacuumed from the top by a suction inlet placed on the upper cover and then is vertically collected in the collection bag. This way, the material is not collected at the entrance and clog inside the suction system is avoided.



## OPTIONALS

- ✓ EARTH GROUNDING
- ✓ STAINLESS STEEL SIEVE GRID
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST