

DBF 20 - INDUSTRIAL THREE PHASE



FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



PACKAGING



- ✓ Side channel blower motor , powerful and silent, totally maintenance free, suitable for continuous duty
- ✓ Low noise level
- ✓ Easy filter replacement
- ✓ Reduced downtime of machine tools
- ✓ Possibility of integration on other vacuum cleaners
- ✓ Modularity is guaranteed to fulfil the client's needs
- ✓ Full customization for specific needs
- ✓ Pressure relief valve for motor protection
- ✓ Long lasting

SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	1,8
Electrical protection	IP	55/F
Max water lift	mmH ₂ O	3000
Max air flow	m ³ /h	270
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	70

FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	8.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - ANT M
Cleaning system		Manual

COLLECTION UNIT

Capacity	lt	25
----------	----	----

VOLUME

Dimensions	cm	4x44x67h
Weight	kg	40



SUCTION UNIT

The suction unit is a side channel blower, with direct coupling between the motor and the impeller fan. It is designed without any transmission system, and is therefore silent, totally maintenance free and suitable for continuous duty operations.



FILTER UNIT

The large surface star antistatic filter, located inside the filter chamber, is made of polyester and provides high resistance against clogging and passage of fine dust. It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment.



COLLECTION UNIT

The unit is manufactured with thick painted steel for improved sturdiness and long-lasting lifetime



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ EARTH GROUNDING